

The present invention has been assigned to Coax Corporation, a Delaware Corporation, by the inventors: Winston W. Hodge and William H. Darnall.

5

10

A METHOD FOR BUFFERING VIDEO, DATA, AND VOICE SIGNALS USING A COMMON SHARED BUS

The present invention is a Continuation-In-Part of patent application 09/162,313 filed on 9/28/98 and titled "Interactive Digital Program Encoder and System".

15

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to a broadband hardware system. More particularly, the present invention is relates a method for buffering of video, data and voice signals in a digital headend.

20

THE PRIOR ART

There are four main types of broadband technologies which include digital television (DTV), satellite , cable and digital subscriber lines (DSL). These four main broadband technologies provide new opportunities for transport and content providers, advertisers, consumer electronics companies, and consumers.

25

Broadband technologies can be classified as either one-way or two-way. One-way technologies send digital information to the end user at very high speeds, but rely on some other means (usually an analog modem and a phone line) to receive information from the end user. One-way broadband technologies include digital television (DTV) and satellite. Two-way broadband technologies, such as cable and digital subscriber lines (DSL) send and receive digital information at very high speeds over the same medium. Two-way broadband technologies usually require a wired infrastructure.

Broadband technologies transfer sounds and images as a series of digital signals which are more noise-immune and reliable than analog communications. Additionally, when compressed data is transferred digitally, it takes up much less space than analog data. This effective increase in bandwidth can be used to provide services which deliver Internet content faster, deliver compelling next generation content like streaming IP, deliver video and data to add interactivity to television, improve the display resolution of traditional TV programming (HDTV), and add more content. Digital transfer allows at least four standard definition channels to occupy the same space that one analog channel occupies today.

Cable companies are in the process of transitioning from a one-way analog broadcast network to a two-way broadband digital network. However, this transition has proven to be costly due to the disparate systems using different communications protocols and the problems associated with system integration. A modular and scalable

headend system which combines voice, data, and video is not presently available to cable companies. Additionally, commercially available headend systems are not readily configurable, thus the commercially available headend systems provide a limited number of services. Generally, present headend systems also have narrow bandwidth back channels which further limits the number of available services. Finally, the present day digital headend equipment can not guarantee the quality of service (QoS) for a broadband network which is configured to provide for the convergence of video, voice, and data communications.

FIG. 1 shows an illustrative prior art digital headend system 10 which is configured to provide two-way broadband communications. The data communicated and processed by the digital headend 10 includes analog video 12, Internet data 14, and digital video 16. An analog video signal 12 is received by a first upconverter 18. Those skilled in the art shall appreciate that the upconverter provides the appropriate RF communication frequency range for downstream transmission via a cable and/or HFC distribution network to a set top box. Additionally, those skilled in the art shall also appreciate that during upstream communications, a QPSK demodulator (not shown) is used to demodulate the upstream signals for communication with the digital headend.

In the digital headend system 10, the Internet data 14 received by the digital headend 10 is communicated to a central processing unit (CPU) 20 and a point-of-presence (POP) cable modem termination system (CMTS) 22. The CPU 20 performs the

function of providing menuing information, conducting accounting and billing, and managing the conditional access control. The CMTS 22 is a data-over-cable service interface specification (DOCSIS) compliant cable headend router which provides an Internet Protocol (IP) standard which allows a plurality of cable modems (not shown) to communicate with the CMTS 22. Downstream data from the CMTS 22 is then communicated to a quadrature amplitude modulation (QAM) modulator 24. The QAM modulator 24 provides a method for modulating digital signals onto an intermediate RF carrier signal involving both amplitude and phase coding which is then communicated to a second upconverter 26. As previously mentioned, the upconverter 26 provides the function of translating QAM modulated data at the appropriate frequency as a plurality of downstream signals. Upstream signals 28 generated by a cable modem (not shown) are then received by a Quadrature Phase-Shift Keying (QPSK) demodulator 30 on the digital headend 10. The QPSK demodulator 10 demodulates digital signals from a RF carrier signal using four phase states to code two digital bits. The digital output from the QPSK demodulator 30 is communicated to the CPU 20 and an out-of-band QPSK modulator 32. The out-of-band (OOB) QPSK modulator 32 provides bi-directional signaling for broadband communications as would be appreciated by those skilled in the art. The OOB QPSK modulator 32 is operatively coupled to an upconverter 34.

The digital video data 16 received by the digital headend 10 is received by the control computer 36 and by a video server 38. Under the guidance of the control computer 36, the video server 38 transmits digital video signals to a QAM modulator 40

which communicates the modulated data to an upconverter 42. The upconverter 42 translates the digital video data at the appropriate downstream frequency for subsequent transmission to a set-top box (not shown). Upstream communications generated by the digital set-top box are communicated to a QPSK demodulator (not shown) which is
5 dedicated to digital video.

The control computer 36 manages the dynamics of digital headend and the Internet data, digital video data and analog data by processing the upstream communications from the set top boxes or cable modems. Further still the control computer 36 determines what
10 movies are loaded onto the video server 38.

It shall be appreciated by those of ordinary skill in the art that an upconverter level adjuster 42 is employed to adjust the level for RF signals communicated by each
15 respective upconverter 18, 34, 42, and 26.

Although not shown, telephony services may also be included in the digital headend shown in FIG. 1. If telephony services were added to the headend described above, they could be provided with a conventional switched telephony system or a voice over IP (VoIP) telephony system. The prior art telephony systems which interface with
20 the digital headend 10 would generally employ downstream QAM modulators with upconverters and upstream QPSK demodulators.

The prior art digital headend system 10 has little or no modularity built into the system. Modularity is defined as the property which provides functional flexibility to a computer system by allowing for the assembling of discrete software units which can be easily joined or arranged with other hardware parts or software units. For example, the prior art digital headend system includes a CMTS 22 which receives Internet data in the form of Ethernet frames using the IP protocol and employs an MPEG-2 transport stream. Additionally, the prior art digital headend 10 includes the digital video 16 which is received as an MPEG-2 transport stream and this MPEG-2 transport stream is also used to communicate the digital video 16 to a set-top box (not shown). Although Internet data and digital video data use the same MPEG-2 transport stream, these two data streams have not been cost effectively integrated. For the co-existence of these two data streams to occur a separate stand alone intermediary hardware and software solution is necessary. The intermediary hardware and software solution does not provide a modular platform.

Therefore, it would be beneficial to provide a digital headend system which can integrate digital video, digital data, digital voice signals and upstream communications signals without the use of an intermediary hardware and software solution.

Furthermore, it would be beneficial to provide a two-way broadband system which can be optimized by using shared resources.

The present invention provides a method for combining a plurality of digital video signals, a plurality of digital data signals, a plurality of voice signals, and a plurality of upstream communications. More particularly, the method comprises providing a video interface for receiving the plurality of digital video signal, providing a data interface for receiving the plurality of digital data signals, and providing a voice interface for receiving the plurality of voice signals.

The method then proceeds to process the plurality of digital video signals, digital data signals and voice signals. After this processing is completed by the digital headend, the plurality of digital video signals is communicated to at least one smart network interface module which is configured to buffer the plurality of digital video signals. Additionally, the plurality of digital data signals is also buffered with at least one smart network interface module. Further still, the plurality of voice signals is also buffered with the at least one smart network interface module.

The buffered plurality of digital video signals, buffered plurality of digital data signals, buffered plurality of voice signals, and plurality of upstream communications are then communicated across a common shared bus. The plurality of upstream communications are generated by at least one set-top box. In an alternative embodiment the upstream communications are generated by at least one set top box and the cable distribution system.

Additionally, communications are optimized for the buffered plurality of digital video signals, the buffered plurality of digital data signals, the buffered plurality of voice signals and the plurality of upstream communications across the common shared bus by using block transfer. Alternatively, the communications across the shared bus may be performed serially.

5

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224

BRIEF DESCRIPTION OF DRAWING FIGURES

FIG. 1 is an illustrative prior art two-way broadband digital headend system.

5 FIG. 2 provides a comparison between an illustrative traditional piecemeal digital headend and a highly integrated computer controlled headend with system buffering in a shared environment.

10 FIG. 3 is a high level block diagram of a cable system having the highly integrated computer controlled headend.

15 FIG. 4 is a detailed block diagram of the highly integrated computer controlled headend with system buffering in a shared environment.

20 FIG. 5 is a flowchart showing the data flow through the highly integrated computer controlled headend with system buffering in a shared environment.

25

30

DETAILED DESCRIPTION OF THE INVENTION

Persons of ordinary skill in the art will realize that the following description of the present invention is illustrative only and not any way limiting. Other embodiments of the invention will readily suggest themselves to such skilled persons having the benefit of this disclosure.

The present invention is a versatile digital cable system that comprises a hardware platform configured to run a plurality of applications for a two-way broadband system.

Referring to FIG. 2 there is shown a comparison between an illustrative traditional piecemeal digital headend 50 and a digital headend 100 of the present invention which is also referred to as a highly integrated computer controlled headend 100. The illustrative prior art digital cable headend hardware system 50 comprise isolated pieces of equipment such as an isolated CMTS system 52, an isolated Video-on-Demand system 54, an isolated Bi-directional signaling system 56, a digital video system 58, a voice over IP system, and a plurality of upconverters 60, an IP router 62 and a LAN switch 64.

By comparison, the highly integrated computer controlled headend 100 includes a system for buffering video, data and voice signals which unifies the digital functions of these prior art individual systems and pieces of equipment. Additionally, the highly integrated computer controlled headend 100 provides a hardware platform which centrally controls all functions in the digital headend and uses the same digital headend

hardware 100 to enable novel applications for the highly integrated computer controlled headend with software, thereby avoiding the need for intermediary hardware platforms.

Referring to FIG. 3 there is shown a high level block diagram of a cable system in which the highly integrated computer controlled headend 100 of the present invention is employed. In the preferred embodiment, the highly integrated computer controlled headend 100 provides the following functions: communicating with a Network Operations Center (NOC) 102; receiving signals from a satellite 104; receiving off-air transmission 106; receiving and transmitting Internet data 108; receiving and transmitting local telephony signals 110 and long distance telephony signals 112, and communicating with a headend system combiner 114.

To perform the functions described above the highly integrated computer controlled headend 100 performs video, data, and voice processing. The video, data, and voice processing performed by the highly integrated computer controlled headend 100 include downstream and upstream signal processing, i.e. bi-directional signal processing. Additionally, the highly integrated computer controlled headend 100 includes a control system which is configured to regulate or "control" the downstream and upstream signal processing.

It shall be appreciated by those skilled in the art having the benefit of this disclosure that the control data processed by the highly integrated computer controlled

headend 100 is NOT solely generated by the highly integrated computer controlled headend 100. Those skilled in the art will recognize that the control data processed by the highly integrated computer controlled headend 100 may also include control data which is provided by other systems communicating with the highly integrated computer controlled headend 100, such as the NOC and the plurality of set-top boxes.

The highly integrated computer controlled headend 100 is an element of a system which will likely include a NOC (not shown), a headend system combiner 114, an analog headend 115, a distribution network 116, and a plurality of set-top boxes 118a through 118n. The headend system combiner 100 is operatively coupled to the highly integrated computer controlled headend 100 and the analog headend 115. The analog headend 115 receives broadcast signals from satellite transmissions 120 or from off-air antenna transmissions 122. Furthermore, the headend system combiner is configured to combine the signals generated by the analog headend 115 with the signals generated by the highly integrated computer controlled headend 100. The headend system combiner is also operatively coupled to the distribution network 116 which includes a plurality of amplifiers, nodes, coaxial cable and/or optical fiber to distribute output from the headend system combiner 114 to one or more set top boxes 118a through 118n.

The one or more set-top boxes 118a through 118n are configured to receive the plurality of digital video, or the plurality of digital data, or the plurality of voice

information. Additionally, the set-top box is configured to generate the plurality of upstream communications.

Referring to FIG. 4 there is shown a detailed block diagram of the highly

5 integrated computer controlled headend 100 which is also referred to as the digital headend. The highly integrated computer controlled headend 100 comprises a shared bus 120 that permits a high level of integration between video, data and voice signals. Digital video signals provide the representation of video signals in a digital format. Digital data signals are generally communicated in compliance with the data-over cable service
10 interface specification (DOCSIS). DOCSIS is the cable modem standard produced by an industry consortium led by Cable Labs. It shall be appreciated by those skilled in the art having the benefit of this disclosure that the MPEG-2 transport stream is, preferably, employed for communicating said digital video signals and said digital data signals. Voice signals are generally communicated as voice over Internet Protocol (VoIP) or
15 conventional switched telephony. VoIP provides the ability carry normal telephony-style voice over an IP-based Internet with POTS-like voice quality. It shall be appreciated by those skilled in the art having the benefit of this disclosure that VoIP can be represented as either digital data signals. It shall also be appreciated by those skilled in the art that VoIP voice signals are generally communicated using the MPEG-2 transport stream,
20 however, conventional switched telephony systems may also be used with the digital headend 100. Therefore, voice signals refers to both VoIP and conventional switched telephony.

Preferably, the shared bus 120 is a parallel bus such as a 32-bit Compact PCI-bus. The 32 bit Compact PCI-bus allows for the use of a combination of off-the-shelf systems which are integrated with downstream modules and upstream modules of the present invention. Since the Compact PCI-bus can only hold a fixed number of modules, a plurality of Compact PCI chassis may be used to satisfy additional system demands, and thereby provide for system scalability. It shall be appreciated by those skilled in the art having the benefit of this disclosure that a 64-bit Compact PCI bus or any other parallel bus may be used. Alternatively, the shared bus 120 may be a high speed serial bus. Regardless of the type of bus employed, it is essential that the bus architecture which provides for the sharing of resources operates in a manner which is open and scalable.

The downstream content which is processed by the highly integrated computer controlled headend 100 is generated by a network operations center (NOC)104, a satellite or off-the-air broadcast 106, an Internet Portal 108, a local telephone company portal 110 and a long distance telephone company portal 112. The NOC 104 provides a variety of different types of information which include content streams for the highly integrated computer controlled headend 100, security procedures such as cryptography, billing information, and post processing work. The satellite or off-the-air broadcast 106 provides the video signals which are communicated using well known RF signalling methods. The portals, i.e. Internet portal 108, local telephone company 110 and long

distance telephone company 112, receive and transmit information to the highly integrated computer controlled headend 100.

An Internet processing and management system 122 is in communication with the NOC 104 and the Internet portal 108. A telephone processing and management system 124 is in communication with the NOC 104, the local telephone company portal 110 and long distance phone company portal 112. Well known Internet and telephone processing and management systems 122 and 124, respectively, have been developed by companies such as Cisco Systems and Texas Instruments. The Internet process and management system 122 provides processing and management for Internet data. The telephone process and management system 124 provides processing and management of either switched telephony or VoIP signals.

Both of the Internet and telephony processing and management systems 122 and 124, respectively, are operatively coupled to the shared bus 120 via a smart network interface module (NIM) 126 and 128, respectively. Preferably, the smart NIMs 126 and 128 provides a first level of buffering which optimizes the bus transfer rate of the shared bus 120. Alternatively, the smart NIMs 126 and 128 reside on a plurality of downstream modules.

It shall be appreciated by those of ordinary skill in the art that a "bus" is a series of tiny wires that run from one chip to another. The shared bus 120 of the present invention

provides an architecture which allows the headend 100 to share headend resources. The shared bus includes address, data and control elements which are communicated in a serial bus or parallel bus. A serial bus has fewer wires and operates generally at a higher speed. A parallel bus has more wires and generally operates at a slower speed. Any
5 combination of a serial bus and parallel bus may also be employed. Preferably, the shared bus employs a 32-bit Compact PCI bus which is a parallel bus.

Although the preferred embodiment of the present invention employs a smart NIM configured to optimize communications across the shared bus, other devices which do not
10 employ a CPU but which provide buffering may also be employed. These devices may include only memory devices which are configured to buffer video, data and voice signals. For purposes of this patent application, the term smart NIM is not restricted to NIM having a CPU. As described in this patent application, the term the smart NIM refers to a controller which is configured to buffer digital information received by that
15 smart NIM. Preferably, the buffered digital information is optimized by the smart NIM for transfer across the shared bus.

The smart NIMs 126 and 128 are coupled to the Internet and telephony processing and management system 122 and 124, respectively, and provide the first level buffering
20 which controls the blocks of data which are communicated across the shared bus 120. Preferably, the smart NIMs 126 and 128 efficiently manage the transmission of bus traffic using block transfer to communicate data across the shared bus 120. By

optimizing the data being transferred across the shared bus 102, the smart NIM avoids efficiency losses caused by serial connections between disparate system components. Judicious data management provided by the smart NIM optimizes communications within the highly integrated computer controlled headend 100 by managing the

5 communications between the various components of the highly integrated computer controlled headend 100.

A service computer 132 is in communication with the NOC 104. The service computer 132 performs the function of managing the conditional access, billing and

10 configuration management. Configuration management determines the type of equipment deployed and its maintenance history. The service computer is a robust dedicated general purpose computer. Communications with the shared bus system 132 are accomplished with a Smart NIM 134 which provides appropriate buffering to optimize communications along the Compact PCI bus 120 as described in the body of

15 this specification.

An MPEG content computer 136 receives the satellite 104 and off-the-air signals 106 and converts these analog signals to digital video signals using, preferably, an MPEG digital format. The MPEG content computer 136 also receives ad insertion feeds and

20 converts these feeds to a digital content stream which are inserted into the local (off-the-air) content and the satellite feed content 106. The digital content generated by the MPEG content computer 136 is then fed to a 10/100 BaseT interface which, preferably,

provides a MPEG-2 transport stream to a smart NIM 138. Additionally, the digital content generated by the MPEG content computer 136 is also fed to a DVB-ASI/SPI interface operatively coupled to a smart NIM 138 which also uses a MPEG-2 transport stream. As previously described, the smart NIM provides the first level buffering which optimizes the bus transfer rate to the shared bus 120.

The control computer 142 receives control information provided by the NOC 104. The control information includes a program guide, generated at the NOC 104, which is communicated by the highly integrated computer controlled headend 100 to a plurality of set-top boxes 118a through 118n. The control computer 142 also performs the real-time functions of content management and resource allocation for the MPEG content streams. The control computer 142 is a relatively quick and robust computer system compared to the service computer 122. The content management regulated by the control computer 142 comprises the MPEG content from a video server 144 and the MPEG content computer 136. The resource allocation provided by the control computer 142 manages system resources for the highly integrated computer controlled headend 100. The control computer is operatively coupled via a 10/100 BaseT interface to a smart NIM 146 which is operatively coupled to the shared bus 120.

The video server 144 receives content from the NOC 104 or from the MPEG content computer 136. The video server 144 provides local storage for digital video. As previously described, the video server 144 is managed by the control computer 142. The

output from the video server 144 is communicated to smart NIMs 148 and 150. The smart NIMs 148 and 150 provide the first level buffering which optimizes the bus transfer rate to the shared bus 120.

5 A plurality of support processors 152 and 154 having appropriate memory resources are resident as modules which are configured to interface with the shared bus 120. Each support processor 152 and 154 is operatively coupled to disk drives 156 and 158, respectively. Each of the support processors 152 and 154 operate as an individual computer which are operatively coupled to the shared bus 120. The support processors 10 152 and 154 contain configuration information for the upstream and downstream modules (described below). Additionally the support processors 152 and 154 and their associated disk drives 156 and 158 also contain software programs for the upstream and downstream modules. The support processors 152 and 154 provide the preferred alternative to managing the addition of software to the highly integrated computer 15 controlled headend 100. By way of example and not of limitation, hundreds of utility programs keep track of time of day, memory addresses, and are responsible for managing the downloading of software to the upstream and downstream modules. When loading software onto the downstream and upstream modules, it is important to avoid loading viruses or other types of software onto the system which will affect the performance of 20 the highly integrated computer controlled headend 100 and the set-top boxes which receive the new software.

More particularly, the process for installing software onto the downstream modules or upstream modules or the set-top boxes includes first receiving software on one of the support processors 152 or 154. The received software is then tested locally on the support processor 152 or 154 to make sure the software is "clean". A downstream or upstream module is then taken out of service and then loaded with the new software. Diagnostics are performed to make sure the module is operating properly. Once the module has successfully passed the self-test, the module is brought back on-line. When the module is taken off-line and put back on-line, one of the support processors communicates the status of the module to the service computer 132. After the completion of loading the software on the appropriate downstream module or upstream module, the support processor may then move onto the next module and proceed in a similar manner as described above. In general each support processor 152 and 154 communicates the status on each of the downstream and upstream modules to the service computer 132 which in turn communicates this information to the network operations center 104.

The highly integrated computer controlled headend 100 also includes an advanced digital down stream data module 160a through 160n and 166. The advanced digital downstream data modules 160a through 160n provide a highly integrated QAM functionality which improves the management of downstream data, increases reliability for the transmission of the downstream data, and provides for better utilization of available bandwidth. The advanced digital downstream data modules 160a through 160n

each comprise a dedicated high-speed embedded processor, an onboard memory, an upconverter, and an automatic level adjuster. The dedicated processor is configured to track the contents of the downstream video, data and voice information and provide refinement in control information. The refinements of control information by the dedicated processor permits data sharing, data muxing, increased security, and improved downstream bandwidth management. It shall be appreciated by those skilled in the art having the benefit of this disclosure that the smart network interface module may be a discrete module operatively coupled to the shared bus or the smart network interface module may be resident on the downstream module, or any combination thereof.

Each advanced digital downstream data module 160a through 160n is operatively coupled to an upconverter 162a through 162n, respectively. The upconverters 162a through 162n have a small footprint and are a highly integrated component of each of the advanced digital downstream data modules 160a through 160n. The small footprint for the upconverter lets the upconverter reside as an extension of the advanced digital downstream data module 160a through 160n, thereby permitting the advanced downstream data module having an upconverter to fit with a single module space shared bus chassis.

The advanced digital downstream data module 160a through 160n is configured to handle video, data and voice signals on the same QAM module. By way of example, and not of limitation, the advanced digital downstream module can be configured to perform

CMTS DOCSIS-compliant modem functions and/or digital video transmissions simultaneously. The advanced digital downstream module may also be managed by software which is configured to mix and integrate different types of data, e.g. IP data signals, digital video signals, within a single platform using the MPEG-2 transport stream.

Preferably, the present invention also includes a bi-directional signaling and control module 164 which includes a downstream out-of-band Quadrature Phase Shift Keying (QPSK) transmitter 166 and an upstream QPSK receiver 168. The bi-directional signaling and control module 164 provides the two-way signaling necessary to communicate between the highly integrated computer controlled headend 100 and a plurality of set-top boxes (not shown). The bi-directional signaling and control module 164 includes a powerful embedded microprocessor which permits local control and management. The downstream out-of-band QPSK transmitter 166 is operatively coupled to an upconverter 170. It shall be appreciated by those of ordinary skill in the art that during out-of-band communications a plurality of control signals are communicated in portions of the broadband spectrum that does not contain program content.

A downstream combiner 172 receives the output from upconverter 162a through 162n and 170 performs the function of combining downstream signals. The downstream combiner 172 is an isolation device which sets gains for downstream transmission, i.e. tilt compensation, and provides system reliability with diagnostic tools. The downstream

combiner 172 includes a plurality of passive and active devices which combine the upconverter 162a through 162n and 170 output. Preferably, the downstream combiner 178 monitors the "health" of each downstream encoder 160a through 160n, the downstream out-of-band QPSK transmitter 166, and their respective upconverters 162a through 162n and 170.

A diplexer 174 receives signals from the downstream combiner 170. The diplexer 174 is a high pass/low pass filter which "high" passes downstream information and "low" passes upstream information. The diplexer receives "high" pass signals from the downstream combiner 172 and submits these signals to a headend system combiner 114.

The headend system combiner 114 is configured to permit combining the signals generated by an existing analog cable headend (not shown) with the modulated digital headend output generated by highly integrated computer controlled headend 100.

Referring to FIG. 3 as well as FIG. 4, the distribution network 116 receives output from the headend system combiner 114. It shall be appreciated by those of ordinary skill in the art that the distribution network includes a plurality of amplifiers and set-top boxes or modems. The set-top boxes are configured to receive signals from the highly integrated computer controlled headend 100 and the analog headend. Upstream communications generated by the set-top boxes are communicated to headend system 114 which submits the upstream communication to diplexer 174. The diplexer 174 low passes the upstream communications to an upstream distribution amplifier 176.

Referring back to FIG. 4, the upstream distribution amplifier 176 receives upstream signals from the diplexer 174. The upstream distribution amplifier 176 provides impedance matching, inverse tilt compensation, and diagnostic services for the distribution network. The upstream distribution amplifier does not demodulate upstream signals.

A plurality of upstream receiver modules 168, 178a through 178n, and 180 through 180n accept upstream data signals from the upstream distribution amplifier 176.

Upstream data signals are communicated in the form of packets which contain the Internet data, telephony data, and system status/control data. Preferably, each upstream receiver module 168, 178a through 178n, and 180 through 180n includes the following components, an upstream tuner, a PCI interface, a microprocessor and memory support, encryption circuits, and buffer amplification. More particularly, upstream receiver module 168 is operatively coupled with the downstream out-of-band QPSK transmitter 166 and receives upstream communications associated with the data signals generated by the downstream out-of-band QPSK transmitter 166. The upstream receiver modules 178a through 178n receive upstream DOCSIS data and demodulated the upstream signal. The upstream receiver modules 180a through 180n receive out-of-band upstream communications from the distribution network and demodulates the upstream signal. Each upstream receiver module modules 168, 178a through 178n, and 180 through 180n

is operatively coupled to the shared bus 120, and submit their demodulated output to control computer 142.

Preferably, a 32 bit Compact PCI-bus is employed. Additionally other parallel
5 buses including a 64-bit bus, 128-bit bus, 256-bit bus and larger shared bus configurations may also be employed. Alternatively a serial bus is also used for the shared bus 120. Additionally, any combination of a parallel and serial bus may also be employed.

10 By having the highly integrated computer controlled headend 100 with the shared bus system, a variable quality of service (QoS) is achieved. The variable QoS differentiates between different types of data and the way the data is handled. By way of example Internet data may have an acceptable degree of delay between packets. However, voice applications can not have too much delay otherwise the quality of the
15 voice signal is compromised. The highly integrated computer controlled headend 100 has the ability to guarantee the delivery of different types of data in a prescribed manner, and thereby meet variable QoS demands.

The highly integrated computer controlled headend 100 creates a highly flexible,
20 scalable, and modular system design which is configured to run various applications. Additionally, the hardware platform can be configured to reduce the number of analog

channels that need to be converted to digital channels thereby optimizing available bandwidth.

The software for the highly integrated computer controlled headend 100 comprises an advanced system software, a digital video broadcast module, and a CMTS headend router software module. The advanced system software wraps around the highly integrated computer controlled headend 100 and controls the advanced digital down stream data module 160a through 160n and the integrated bi-directional signaling and control module 164. In addition, the advanced operating system software creates an applications program interface (API) where external software modules can be inserted and used to run digital applications.

The digital video broadcast module expands the number of broadcast channels it offers and needs only the advanced digital down stream data module to be operational.

This module is compatible with the plurality of digital set-top boxes.

The CMTS headend router software module is used to control and manage the advanced digital down stream data module and the integrated bi-directional signaling and control module. The CMTS headend router software provides router functionality to the highly integrated computer controlled headend by controlling encoding, encapsulation, error correction, handshaking, and communications protocols used by DOCSIS.

Alternatively, it shall be appreciated by those skilled in the art having the benefit of this disclosure that each of the individual smart NIMs 126, 128, 134, 138, 140 146, 148 and 150 can be combined in an aggregated smart NIM 130. Furthermore, it shall be appreciated by those skilled in the art having the benefit of this disclosure that any
5 combination of individual smart NIMs and aggregated smart NIMs can be used to accomplish the same objective as described herein.

Referring to FIG. 5 there is shown a flowchart which describes the method or process 200 for combining digital video signals, digital data signals, voice signals, and upstream communications in a shared system environment described in FIG. 4. Referring
10 to FIG. 4, the shared environment includes the shared bus 120 and buffers the various information streams within each of the smart NIMs 126, 128, 134, 138, 140 146, 148 and 150, or in the aggregated smart NIM 130. The method of combining these different information streams in the highly integrated computer controlled headend 100 is described in further detail below.

15

In block 210, the method or process for buffering various information streams in a shared environment is engaged by: providing a video interface for receiving digital video signals; providing a data interface for receiving digital data signals; and providing a voice interface for receiving voice signals. It shall be appreciated by those skilled in the art
20 having the benefit of this disclosure that each of the different information streams, i.e.

video, data and voice, have a plurality of associated control signals associated with each different information stream.

The video interface provides an interface for the highly integrated computer controlled digital headend 100 to receive analog video signals and communicate digital video signals. The analog video signals and digital video signals include control analog video signals and control digital video signals, respectively. The analog video signals are generated by satellite 104 and off-air communications 106. The digital video signals are communicated between the digital headend and the NOC 102. The data interface provides an interface for the digital highly integrated computer controlled headend 100 which communicates digital data signals from one or more Internet portals 108 with the digital headend 100. The digital data signals include control digital data signals. The voice interface provides an interface for the digital headend which communicates voice signals from the local telephone company portal 110 and the from the long distance telephone company portal 112. The voice signals include control voice signals.

At block 212, the digital video signals and analog video signals are processed. Preferably, the video signals are processed by the video server 144, the control computer 142, newly converted MPEG2 content computer 136, and the service computer 132. As described above, the video server 144, the control computer 142, newly converted MPEG2 content 136, and the service computer 142 are operatively coupled to smart NIMs 126, 128, 134, 138, 140 146, 148 and 150 having 10/100BaseT interfaces and

DVB-ASI/SPI interfaces as previously described, or in the alternative an aggregated smart NIM 130 or any combination thereof.

At block 214, the digital data signals are processed. As described above, the digital data signals are processed by the Internet processing and management computer 122. The Internet processing and management computer is operatively coupled to a smart NIM 126 or in the alternative an aggregated smart NIM 130 or any combination thereof.

At block 216, the voice signals are processed. As described above, the voice signals are processed by the Telephony processing and management computer 124. The Telephony processing and management computer is operatively coupled to a smart NIM 128 or in the alternative an aggregated smart NIM 130 or any combination thereof.

At block 218, buffering the digital video signals with at least one smart NIM is performed. Each smart NIM performs the function of buffering digital video signals including control digital video signals and generates buffered digital video signals. The buffered digital video signals are transmitted and received from the shared bus. Preferably, the buffered digital video signals are communicated across the shared bus in a parallel fashion. Alternatively, the buffered digital video signals are communicated using a serial bus, or any combination of a serial bus and a parallel bus.

At block 220, buffering the digital data signals with at least one smart NIM is performed. The smart NIM performs the function of buffering digital data signals including control digital data signals and generates buffered digital data signals. The buffered digital data signals are transmitted and received from the shared bus.

- 5 Preferably, the buffered digital data signals are communicated across the shared bus in a parallel fashion.

At block 222, buffering the voice signals with at least one smart NIM is performed. The smart NIM performs the function of buffering voice signals including
10 control voice signals and generates buffered voice signals. The buffered voice signals are transmitted and received from the shared bus. Preferably, the buffered voice signals are communicated across the shared bus in a parallel fashion. Alternatively, the buffered digital video signals are communicated using a serial bus, or any combination of a serial bus and a parallel bus.

15

At block 224, the alternative buffering of the digital video signals, digital data signals, and voice signals can be performed by an aggregated smart NIM 130. The aggregated smart NIM 130 provides the same functionality as described by blocks 218, 220, and 222. It shall be appreciated by those skilled in the art that any combination of
20 smart NIMs could also be employed to perform the buffering, including the alternative NIMs resident on the downstream modules.

As described in FIG. 4, the digital headend preferably includes a plurality of smart NIMs or in the alternative an aggregated smart NIM or any combination thereof. The smart NIM is generally defined as a network interface module having an onboard CPU and having a plurality of memories to support buffering. The plurality of memories refer
5 to the L1 cache, L2 cache and RAM and any other such memories.

The preferred embodiment of the present invention includes a smart NIM which can also provide the functionality of optimizing data transfer across the shared bus 120. Preferably, the smart NIM performs the operation of optimizing data transfer by
10 judiciously employing the memory buffering available on the smart NIM to maximize the data flow across the shared bus. More particularly, the smart NIM operations optimize the data transfer across the shared bus by communicating information from the various data streams in parallel across the system bus. Therefore, the various information streams can access the shared bus simultaneously.

15

It shall be appreciated by those of ordinary skill in the art that a "bus" is a series of tiny wires that run from one chip to another. The shared bus 120 of the present invention provides an architecture which allows the headend 100 to share headend resources. The shared bus includes address, data and control elements which are communicated in a
20 serial bus or parallel bus. A serial bus has fewer wires and operates generally at a higher speed. A parallel bus has more wires and generally operates at a slower speed. Any

combination of a serial bus and parallel bus may also be employed. Preferably, the shared bus employs a 32-bit Compact PCI bus which is a parallel bus.

Although the preferred embodiment of the present invention employs a smart NIM
5 configured to optimize communications across the shared bus, other devices which do not employ a CPU but which provide buffering may also be employed. These devices may include only memory devices which are configured to. For purposes of this patent application, the term smart NIM is not restricted to NIM having a CPU. As described in this patent application, the term the smart NIM refers to a NIM which is configured to
10 buffer digital information received by the NIM. Preferably, the buffered digital information may be optimized by the smart NIM for transfer across the shared bus.

At block 226, the communications across the shared bus are performed. As described in FIG. 4, due to cost constraints the shared bus 120 is preferably a 32-bit
15 Compact PCI bus. Alternatively, the buffered digital video signals are communicated using a serial bus, or any combination of a serial bus and a parallel bus. It shall be appreciated by those skilled in the art that the alternative bus architecture may be employed. The communications which are performed across the shared bus are two-way communications. Downstream communications which are buffered and optimized by the
20 smart NIMs 126, 128, 134, 138, 140 146, 148 and 150 and in the alternative aggregated smart NIM 150 are communicated across the shared bus to a downstream module 160a through 160n. Upstream communications are also communicated across the shared bus.

Upstream communications are generated by at least one set-top box and demodulated before being communicated across the shared bus, and then transmitting the upstream communications to the smart NIMs 126, 128, 134, 138, 140 146, 148 and 150 and in the alternative aggregated smart NIM 130, or downstream module 160a through 160n.

5

At block 228, downstream buffering is performed. Preferably the downstream buffering is performed so that the downstream modulation is optimized. Preferably, the downstream signal which is buffered is configured as an MPEG-2 transport stream.

Additionally, the downstream buffering provides for the addition of control data to the
10 MPEG-2 transport stream. Control data is added to the MPEG-2 transport stream in a process which spreads the MPEG-2 data packets apart. After having spread the MPEG-2 data packets apart one or more control data packets are added. The new control data packets include and providing for the addition of control data packets. The control data packets added to the MPEG-2 transport stream include URLs, indicia of interest,
15 overlays, targeted advertising, and other data which can be used in an interactive environment. It shall be appreciated by those skilled in the art having the benefit of this disclosure that the smart network interface module may be a discrete module operatively coupled to the shared bus or the smart network interface module may be resident on the downstream module, or any combination thereof.

20

At block 230, downstream modulation is performed. The downstream modulation includes QAM, QPSK and any other such modulation scheme in which digital data is

converted to an analog carrier signal. It shall be appreciated by those skilled in the art having the benefit of this disclosure that additional functions such as forward error correction are also employed during the process of downstream modulation.

5 At block 232, downstream signals are combined. Preferably, the downstream signals are combined at the downstream combiner 172 and at the headend system combiner 114. Preferably, the process of combining video, data and voice signals also includes combining the modulated digital signals with the downstream combiner 114. Preferably, the headend system combiner 114 combines the analog headend output 115
10 with the output from the downstream combiner 172 for transmission via the distribution network 116.

At block 234, the downstream signals are communicated across a distribution network. The distribution network includes cable only distribution networks, hybrid fiber
15 cable systems, wireless systems, and any other such distribution network.

At block 236, a set-top box receives the downstream signals from the distribution network and communicates the downstream signals to a display screen. A user may then interact with the downstream signal by generating an upstream communication in a
20 manner consistent with systems and methods well known to those skilled in the art. Generally, the upstream communications generated by a user includes information submitted by the user to the set-top box. Preferably the upstream communications

includes a plurality of test signals. The plurality of test signals are used to determine the noisy upstream channels and the upstream channels that have little or no noise.

At block 234, the upstream communication is communicated to the digital head
100 end by way of the distribution network 116. Preferably, the upstream
communication includes a plurality of test signals as described above. Preferably, the
distribution network is configured to use the test signals generated by the set-top boxes to
determine the which channels are noisy and which channels have little or no noise and
which channels with little or no noise are available for upstream communications.

At block 238, the upstream communication with the test signals are processed and
a final assessment is made of which channels are noisy, which channels have little or no
noise, and which channels have available bandwidth for upstream communications. The
results generated by the test signals are then included in the upstream communications
signals. Therefore, in the preferred embodiment, the upstream communication signals
generated by the set-top box includes information submitted to the set-top box, the test
signals, and the results generated by the test signals.

At block 240, the upstream communication signals are demodulated and
communicated across the shared bus 120 to the smart NIM 126, 128, 134, 138, 140 146,
148 and 150 or in the alternative the aggregated smart NIM 130 for buffering.
Furthermore, the upstream communication signals are also parsable into user generated

set-top box signals, and distribution test signals. User generated set-top box upstream signals are communicated across the shared bus to the smart NIM which then communicates the upstream signals to the video, data, or voice processing. The distribution test signals are communicated to the downstream buffering block via the shared bus 120. The distribution test signals are then incorporated in the downstream channel and communicated to the set-top box to optimize the use of the upstream channels.

It shall be appreciated by those of ordinary skill in the art having the benefit of this disclosure that although a reference is made to only one set-top box, a distribution network includes a plurality of set-top boxes. Additionally, it shall be appreciated by those of ordinary skill in the art having the benefit of this disclosure that the set-top box referred to in this specification also refers to a "cable modem."

While embodiments and applications of this invention have been shown and described, would be apparent to those skilled in the art that many more modifications than mentioned above are possible without departing from the inventive concepts herein. The invention, therefore, is not to be restricted except in the spirit of the appended claims.